

RhinoAg: Turf Mowers

X SERIES - RIGID



Ideal for contractors, sod farms, polo clubs, and local government



Simple height adjustment from 1/2" - 5" for versatile and year-round mowing



Designed for tractors with 50-65 PTO HP



100% gear driven, no belts



Sealed internal roller bearings for total protection against moisture, soil, and debris



Full-length rollers follow the ground contour, prevent scalping, and produce perfect stripes



Body produced from 8 gauge Strenx® 700MC and hot dipped galvanized



Smaller cutting width ideal for compact applications that still need a professional finish

RHINOAG

RhinoAg: Specifications

X SERIES - RIGID

Specifications	X603	X804
Cutting Width	6' 3"	8'
Transport Width	6' 6"	8' 2"
Overall Length	4' 3"	
Cutting Height	Up to 5"	
Hitch	Lift -Type	
Blade Carrier	3 1/4" x 3/8" spring steel, hardened and tempered	
No. of Blades	6	8
Blades	3" x 1/4" spring steel ground edged parallel hardened and tempered, pivoting on high tensile pivot bush assembly	
Rotors	3	4
Mowing Rates	5.3 acres/hr @ 7mph	6.7 acres/hr @ 7mph
Blade Overlap	2 1/2"	
PTO HP Required (Min)	50 HP	65 HP
Tractor PTO	540 RPM	
Output Shaft Diameter	1 1/2" (40mm)	
Gearbox Oil	85W-140 factory filled	
Blade Tip Speed	14,764 FPM	
Drivelines	CAT4 - 1 3/8" 6-spline	
Deck Thickness	8 gauge Strenx® 700MC folded mono-coque construction with reinforcement and underside trough is 8 gauge Strenx® 700MC	
Weight	1,047 lb.	1,235 lb.



ROLLER BEARINGS

Sealed internal roller bearings offer total protection against moisture, soil, and debris



LONG-LASTING BLADES

Produced from 1/4" sprung steel to offer hours of continuous work without needing to sharpen



STRENX

High-performance 700MC structural steel

