



LAND LEVELERS



22" LAND LEVELER LL22L/LL22T
LIFT ONLY OR TILT & LIFT MODELS
SIZES: 6', 7' & 8' BOX
DIMENSIONS: 22" HIGH X 25" DEEP



MAX HP 50
18.5" X 8.5" X 8 WHEELS WITH TIRES INCLUDED, 5 ON 4.5 EASY LUBE HUB
UNIT IS COMPLETE WITH CYLINDERS AND HOSES

REPLACEABLE HIGH CARBON STEEL DOUBLE SIDED CUTTING EDGE



32" LAND LEVELER LL32L/LL32T
LIFT ONLY OR TILT & LIFT MODELS
SIZES: 10', 12' & 14'
BOX DIMENSIONS: 32" HIGH X 50" DEEP



CONSTRUCTED OF ALLOY STEEL
STANDARD 15" X 8" WHEEL, OTHER WHEELS AVAILABLE
6 BOLT HUB WITH GREASE FITTINGS
UNIT IS COMPLETE WITH

CYLINDERS AND HOSES

REPLACEABLE HIGH CARBON STEEL DOUBLE SIDED EDGE

INCLUDES STANDARD PIPE MOUNT JACK, ADJUSTABLE HITCH WITH SINGLE OR DOUBLE TONGUE



42" LAND LEVELER LL42T
SIZES: 12', 14', 16', 18' & 20'

APPROXIMATE WEIGHTS: 12' – 6,000 IBS., 14' – 6,200 IBS., 16' – 6,400 IBS., 18' – 6,800 IBS., 20' – 7,000 IBS.

BOX DIMENSIONS: 42" HIGH X 54" DEEP

INDEPENDENT LIFT ARMS FOR LEFT AND RIGHT TILTING, OSCILLATING ROCKER ARM WITH GREASABLE BUSHINGS

STANDARD 15" X 8" WHEELS FOR 12', 14' AND 16' MODELS, 15" X 10" WHEELS FOR 18' AND 20' MODELS, 6 BOLT HUB WITH GREASE FITTINGS

UNIT IS COMPLETE WITH CYLINDERS AND HOSES, REPLACEABLE HIGH CARBON STEEL DOUBLE SIDED CUTTING EDGE

PIVOTING SINGLE TONGUE HITCH, INCLUDES STANDARD PIPE MOUNT JACK

THREE SPOOLS HYDRAULIC REQUIREMENTS: TWO SPOOLS FOR TILT, ONE SPOOL FOR LIFT

48" LAND LEVELER - LL48T

SIZES: 20' & 24' / APPROXIMATE WEIGHT 9,500 IBS.

BOX DIMENSIONS: 48" HIGH X 60" DEEP, STANDARD 15" X 10" X 8 BOLT WHEELS, CONSTRUCTED SIMILAR TO TLL42 MODEL



WATCH THE NOTCH LAND LEVELER DEMOS ON OUR WEBSITE

WWW.NOTCHMFGINC.COM