

RhinoAg: Boom Mowers

▶ DB150



1" cut capacity



Cat 2 & 3 Quick Hitch compatible
(with adapter kit)



Perfect for cutting around the farm, ranch,
or homestead



Arm extends 158" from centerline



Optional rear or side mount gauge wheel
available



119" transport width



Mower head has 175° range of motion
(85° up/90° down)



60" cutting width

DB150

Specifications	DB150
Cutting Width:	5'
Transport Width:	119"
Overall Width (Head):	65 1/4"
Overall Length (Head):	71 3/8"
Cutting Height (Min):	1"
Hitch:	CAT 2 & 3 QH compatible w/ adapter kit
Speed Inserter:	Driveline mounted
Blade Carrier:	Pan
Blades:	1/2" x 4" updraft
Blade Rotation:	Clockwise
HP Required:	60 w/ adequate front wt.
Tractor PTO Speed:	540 RPM
Oil Reservoir Capacity:	55 gallons - factory filled
Max System Pressure:	3,000 PSI
Blade Tip Speed:	16,870 FPM
Horizontal Reach (Max):	158" from center of tractor
Extension Cylinder Stroke:	30"
Cutting Capacity (Max):	1"
Driveline Size:	CAT 4
Overload Protection:	Relief valve
Deck Thickness:	10 Ga
Side Skirt:	10 Ga x 9 1/4"
Range of Head Movement:	85° Up / 90° Dn
Hydraulic Pump Capacity:	18.32 GPM
Skid Shoes:	Replaceable
Safety Deflectors:	Rubber deflectors or chain guards
Weight (Approx):	2,150 lbs w/ oil



GAUGE WHEELS

Optional gauge wheels guide the mower head over uneven terrain reducing gouging



EASY TRANSPORT

from site to site with a 119" transport width